


# Constant climate chamber HPP Energy efficient with Peltier technology

Model sizes: 110, 260, 400 NEW, 750, 1060 NEW, 1400 NEW Setting temperature range\*: up to +70 °C (HPP110 - 1060) | up to +60 °C (HPP1400) Setting range humidity\*: 10 to 90 % rh (HPP110 - 1060) | 10 to 80 % rh (HPP1400)



# Temperature-humidity working range HPP (%) Alphund 2016 Temperature of humidity test points defined in the guideline ICH



By the way: the Memmert customisation department has already developed different customised models in cooperation with industry experts, for example as an appliance that tests the melting behaviour of ice cream. Contact us at myAtmoSAFE@memmert.com

# ENERGY SAVING, LONG-TERM STABILITY AND MAINTENANCE FREE

## Main fields of application

The most common applications of Memmert HPP appliances are stability testing in accordance with ICH, GMP or IFSCC in the pharmacology, cosmetics and food industry as well as climate-controlled storage and conditioning. Thanks to its smooth and quiet operation, the constant climate chamber is also perfect for growing protein crystals and plants as well as for breeding insects or zebrafish and for keeping mice. The optional, innovative LED lighting guarantees natural growth conditions.

### Reducing operating costs by up to 90 %

In most cases, stability tests are done close to ambient temperature. The Memmert heating and cooling concept using Peltier elements is especially economical for this purpose. Compared to a standard constant climate chamber, it can reduce the energy consumption by up to 90 % during continuous operation over several months.

Technical data of the Memmert constant climate chambers HPP						
Model sizes	HPP110	HPP260	NEW HPP400	HPP750	NEW HPP1060	NEW HPP1400
Volume approx. I	108	256	384	749	1060	1360
External dimensions (WxHxD) mm	745x864x674	824x1183x774	824x1720x788	1224x1726x874	1224x1661x1139	1435x1968x1055
Setting temperature range °C without light, without humidity	0 to +70*					+15 to +60*
Setting temperature range °C without light, with humidity	+5 to +70*					+15 to +60*
Setting range humidity % rh without light/with light	10 to 90/10 to 85 10 to 90/-					10 to 80/-

<sup>\*</sup> Working-temperature range at least 20/10 °C (HPP110 – 1060/HPP1400) below ambient temperature, Deviation with light (HPP110 – 750)

For detailed technical data, please see the Memmert climate chamber brochure or visit www.memmert.com/en/hpp.

